

Title Terms: PRINT; MULTICOLOUR; DESIGN; HEAT; SEAL; FILM
 Derwent Class: A35; A93; F07; F09; G05; P42; P73; P75; P78; T04
 International Patent Class (Main): B41M-005/035; B44C-001/165; B44C-001/17
 International Patent Class (Additional): B05D-001/14; B05D-001/16;
 B32B-005/22; B44C-001/18; D06P-005/28; D06Q-001/00; D06Q-001/14
 File Segment: CPI; EPI; EngPI

1/5/5

DIALOG(R) File 351:Derwent WPI
 (c) 2003 Thomson Derwent. All rts. reserv.

010026666 **Image available**

WPI Acc No: 1994-294379/199436

XRAM Acc No: C94-134274

XRPX Acc No: N94-231506

Laminated applique for applying to a textile substrate - has a layer of flock fibres flocked in a desired motif or pattern onto an adhesive applied to one side of a plastic sheet material

Patent Assignee: HIWELD LTD (HIWE-N)

Inventor: KAY C; LION J P

Number of Countries: 048 Number of Patents: 005

Patent Family:

Patent No	Kind	Date	Applicat No	Kind	Date	Week
WO 9419530	A1	19940901	WO 94IE8	A	19940222	199436 B
AU 9460431	A	19940914	AU 9460431	A	19940222	199502
EP 685014	A1	19951206	EP 94906990	A	19940222	199602
			WO 94IE8	A	19940222	
EP 685014	B1	19970521	EP 94906990	A	19940222	199725
			WO 94IE8	A	19940222	
DE 69403323	E	19970626	DE 603323	A	19940222	199731
			EP 94906990	A	19940222	
			WO 94IE8	A	19940222	

Priority Applications (No Type Date): IE 93122 A 19930222

Cited Patents: FR 2659094; GB 2010123; GB 2245220; US 465478; US 5059452

Patent Details:

Patent No Kind Lan Pg Main IPC Filing Notes

WO 9419530 A1 E 17 D06Q-001/14

Designated States (National): AT AU BB BG BR BY CA CH CN CZ DE DK ES FI
 GB HU JP KP KR KZ LK LU LV MG MN MW NL NO NZ PL PT RO RU SD SE SK UA US
 UZ VN

Designated States (Regional): AT BE CH DE DK ES FR GB GR IE IT LU MC NL
 OA PT SE

AU 9460431 A D06Q-001/14 Based on patent WO 9419530

EP 685014 A1 E D06Q-001/14 Based on patent WO 9419530

Designated States (Regional): AT BE CH DE DK ES FR GB GR IE IT LI LU MC
 NL PT SE

EP 685014 B1 E 10 D06Q-001/14 Based on patent WO 9419530

Designated States (Regional): AT BE CH DE DK ES FR GB GR IE IT LI LU MC
 NL PT SE

DE 69403323 E D06Q-001/14 Based on patent EP 685014

Based on patent WO 9419530

Abstract (Basic): WO 9419530 A

An applique comprises a layer of flock fibres (5a:5b) flocked in a desired motif or pattern onto an adhesive (4) applied to one side of a plastic sheet material (3). The adhesive is applied through screens only in the areas to which the fibres are to be flocked and the flock fibres of at least two different colours are be flocked onto the

adhesive in a desired pattern sequentially through separate screens. Pref. the base layer is a PVC sheet and the flock fibres are polyamide fibres. The adhesive to be of a type compatible with both the flock fibre and the base material. The applique can be complete with a support base (2) of stiff paper, peelably attached to the underside of the base layer.

USE/ADVANTAGE - A multi colour applique for applying to a textile substrate. Provides an applique which has high colour fastness and stability after washing and also having high light fastness and abrasion resistance and pleasant tactile properties.

Dwg.1/3

Title Terms: LAMINATE; APPLIQUE; APPLY; TEXTILE; SUBSTRATE; LAYER; FLOCK; FIBRE; FLOCK; MOTIF; PATTERN; ADHESIVE; APPLY; ONE; SIDE; PLASTIC; SHEET; MATERIAL

Derwent Class: A35; A97; F07; G05; P73

International Patent Class (Main): D06Q-001/14

International Patent Class (Additional): B32B-005/08

File Segment: CPI; EngPI